MEAN WELL
SWITCHING POWER SUPPLY

D-60 SERIES

- LOW COST, HIGH RELIABILITY
- 105℃ OUTPUT CAPACITOR
- INTERNATIONAL AC INPUT RANGE
- BUILT IN EMI FILTER, LOW RIPPLE NOISE
- HIGH EFFICIENCY, LOW WORKING TEMPERATURE
- SOFT-START CIRCUIT, LIMITING AC SURGE CURRENT
- SHORT CIRCUIT, OVERLOAD, OVERVOLTAGE PROTECTED
- COMPACT SIZE, LIGHT WEIGHT
- 100% FULL LOAD BURN-IN TEST



MODEL / SPECIFICATION	D-60A		D-60B	
	CH1	CH2	CH1	CH2
DC OUTPUT VOLTAGE	5V	12V	5V	24V
OUTPUT V. TOLERANCE	±2%	±6%	±2%	±5%
OUTPUT RATED CURRENT	4A	3A	3A	1.8A
OUTPUT CURRENT RANGE	0.3-6A	0.2-4A	0.3-6A	0.2-2.2A
RIPPLE & NOISE (p-p)	50mVp-p	100mVp-p	50mVp-p	100mVp-p
LINE REGULATION	±0.5%	±1%	±0.5%	±0.5%
LOAD REGULATION	±0.5%	±4%	±0.5%	±4%
DC OUTPUT POWER	56W		58W	
EFFICIENCY	73%		76%	
DC VOLTAGE ADJ.	CH1:+10,-5%		CH1:+10,-5%	
INPUT VOLTAGE RANGE	85～264VAC			
INPUT FREQUENCY	47～63Hz			
AC CURRENT	2A/115V 1A/230V			
INRUSH CURRENT	COLD START 25A/115V 50A/230V			
OVERLOAD PROTECTION	105%～150% TYPE:FOLDBACK CURRENT SHUTDOWN RECOVERY:AUTO			
OVER V. PROTECTION	CH1:5.75～6.75V			
OVER TEMP. PROTECTION	-----			
TEMP. COEFFICIENT	±0.03% / ℃ ON +5V OUTPUT			
SETUP,RISE,HOLD UP TIME	800ms, 50ms, 10ms/115VAC 300ms, 50ms, 80ms/230VAC			
WITHSTAND VOLTAGE	I/P-O/P:3KV(NOTE:7) I/P-FG:1.5KV O/P-FG:0.5KV 1min.			
WORKING TEMP.,HUMIDITY	-10℃～+60℃, 20%～90% RH (REFER TO OUTPUT DERATING CURVE)			
STORAGE TEMP.,HUMIDITY	-20℃～+85℃, 10%～95% RH			
DIMENSION	159*97*38mm CASE:901			
WEIGHT	0.55Kgs			
SAFETY	UL1012, TUV EN60950 (IEC950, UL1950) APPROVED			
EMC	CISPR22 (EN55022) CLASS B, IEC801-2,3,4, IEC555-2 VERIFICATION			

NOTE:
1. ALL PARAMETERS ARE SPECIFIED AT 230VAC INPUT, RATED LOAD, 25℃ AMBIENT.
2. TOLERANCE : INCLUDE SET UP TOLERANCE, LINE REGULATION, LOAD REGULATION, CROSS REGULATION.
3. RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR.
4. LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.
5. LOAD REGULATION IS MEASURED FROM 20% TO 100% RATED LOAD, AND ALL OTHER OUTPUTS AT 60% RATED LOAD.
6. EACH OUTPUT PROVIDE UP TO MAXIMUN CURRENT, BUT TOTAL LOAD CAN NOT EXCEED MAX OUTPUT POWER.
7. C2,3,6 MUST BE REMOVED.

BLOCK DIAGRAM



fosc : 54KHz

OUTPUT DERATING



STATIC CHARACTERISTICS



DIMENSION (mm)

- CASE : 901
- TERMINAL PIN NO. ASSIGNMENT
  - PIN 1,2 : AC INPUT
  - PIN 3 : FG ⏚
  - PIN 4 : DC OUTPUT +V2
  - PIN 5 : DC OUTPUT +V1
  - PIN 6,7 : DC OUTPUT COM